### 1. Handling

Unit Volume / Weight

Unit Ref : LG5 Volume : 0.754 m³ Weight : 1775 kg

- Weight is based on 2,350 kg/m³
- Lifting system is by means of a 180mm long spherical pin anchor rated at 5.0 tonnes with a safety factor of 3.
- Lifting is achieved by use of a 5.0t rated pin anchor ring clutch or combination ring clutch only and should comply with the Lifting Operation & Lifting Equipment Regulations 1998 (LOLER).
- Lifting Pin Characteristics

Anchor Type: T-050-0180
Anchor Length: 180mm
dia: 20mm
Foot dia: 50mm
Load Class: 5.0 tonnes

#### **IMPORTANT NOTE:**

Prior to lifting older / pre-used blocks, check the lifting pin for wear / corrosion and check the block for cracks. If the block is cracked or the pin is worn, it could fail when lifting.

### 2. Concrete

- Characteristic 28 day cube strength = 50 N/mm² min.
- Concrete is Class A1 Fire Resistant in accordance with clause 4.3.4.4 of EN 13369

# 3. Manufacture

Manufactured to : BS EN 13369 : 2013
Tolerances to : BS EN 13670 : 2009

## 4. Physical & Chemical Properties

Appearance : Grey in Colour


Other Chemical Properties : Not Applicable

### 5. Design

• Design Life: >100 years

### 6. Manufacture Tolerances

Length ±5mm
 Width ±5mm
 Height ±5mm



В 12.03.20 Registered Trademark ® added to the drawing. CTC RMD Α 03.01.18 CTC RMD Drawing revised & updated 20.01.23 Title block & notes updated. CTC RMD 0 23.06.16 For Information. CTC RMD DRN APP REV DRN DATE **REASON FOR ISSUE** DATE REASON FOR ISSUE APP

Legato® Interlocking Concrete Block
1200mm x 800mm x 800mm (Female Interlocks)

Elite Product Code : LG5

CTC CHKD RMD DATE

23-06-16

ELITE PRECAST CONCRETE LTD
HALESFIELD 9, TELFORD
SHROPSHIRE TF7 4QW
www.eliteprecast.co.uk

SIZE A3 SCALE 1:10



EPC-LEG-005\_D - 1200 x 800 x 800 (LG5)