Unit Volume / Weight

1. Handling

Unit Ref: LG9 0.757 m³ Volume: 1800 kg Weight:

- Weight is based on 2,350 kg/m³
- Lifting system is by means of a 180mm long spherical pin anchor rated at 5.0 tonnes with a safety factor of 3.
- Lifting is achieved by use of a 5.0t rated pin anchor ring clutch or combination ring clutch only and should comply with the Lifting Operation & Lifting Equipment Regulations 1998 (LOLER).

Lifting Pin Characteristics

Anchor Type: T-050-0180 Anchor Length: 180mm 20mm Foot dia: 50mm Load Class: 5.0 tonnes

IMPORTANT NOTE:

Prior to lifting older / pre-used blocks, check the lifting pin for wear / corrosion and check the block for cracks. If the block is cracked or the pin is worn, it could fail when lifting.

REASON FOR ISSUE

2. Concrete

- Characteristic 28 day cube strength = 50 N/mm² min.
- Concrete is Class A1 Fire Resistant in accordance with clause 4.3.4.4 of EN 13369

3. Manufacture

Manufactured to: BS EN 13369:2013 Tolerances to: BS EN 13670: 2009

4. Physical & Chemical Properties

Appearance: Grey in Colour


Other Chemical Properties: Not Applicable

5. Design

>100 years Design Life:

6. Manufacture Tolerances

Length ±5mm Width ±5mm Height ±5mm



1600mm x 800mm x 800mm (Female Interlocks)

Elite Product Code: LG9

DRN CTC CHKD RMD DATE

CTC

CTC

DRN APP

RMD

RMD

03.01.18

23.06.16

DATE

0

DRN APP REV

Drawing revised & updated.

REASON FOR ISSUE

For Information.

SHROPSHIRE TF7 4QW

DRG EPC-LEG-009

SIZE A3 SCALE 1:10

www.eliteprecast.co.uk

23-06-16

DATE